

20EZ7

High-Mu Twin Triode

9-PIN MINIATURE TYPE

For High-Gain, Resistance-Coupled, Low-Level Audio-Amplifiers Operating at Low-Signal Levels, such as Preamplifiers for Low-Cost Stereophonic Phonographs

GENERAL DATA

Electrical:

Heater, for Unipotential Cathodes:

Voltage (AC or DC). 20 volts

Current $0.1 \pm 6\%$ amp

Direct Interelectrode Capacitances (Approx.):^a

	Unit No. 1	Unit No. 2	
Grid to plate	1.5	1.5	μf
Grid to cathode and heater. . .	1.6	1.6	μf
Plate to cathode and heater . .	0.2	0.3	μf

Characteristics, Class A₁ Amplifier (Each Unit):

Plate Voltage	100	250	volts
Grid Voltage.	-1	-2	volts
Amplification Factor.	100	100	
Plate Resistance (Approx.). . . .	80000	62500	ohms
Transconductance.	1250	1600	μmhos
Plate Current	0.5	1.2	ma

Mechanical:

Operating Position. Any

Maximum Overall Length. 2-3/16"

Maximum Seated Length 1-15/16"

Length, Base Seat to Bulb Top (Excluding tip). . 1-9/16" $\pm$ 3/32"

Diameter. 0.750" to 0.875"

Dimensional Outline See *General Section*

Bulb. T6-1/2

Base. Small-Button Noval 9-Pin (JEDEC No. E9-1)

Basing Designation for BOTTOM VIEW. 9PG ←

Pin 1—Heater

Pin 2—Heater

Pin 3—Internal Connection—Do Not Use

Pin 4—Cathode of Unit No. 2


Pin 5—Grid of Unit No. 2

Pin 6—Plate of Unit No. 2

Pin 7—Plate of Unit No. 1

Pin 8—Grid of Unit No. 1

Pin 9—Cathode of Unit No. 1



AMPLIFIER — Class A₁

Values are for Each Unit

Maximum Ratings, Design-Maximum Values:

PLATE VOLTAGE. 330 max. volts

← Indicates a change.



RADIO CORPORATION OF AMERICA
Electron Tube Division
Harrison, N. J.

DATA 1
5-61

20EZ7

GRID VOLTAGE:

Negative-bias value. 55 max. volts
Positive-bias value. 0 max. volts
PLATE DISSIPATION. 1.2 max. watts

PEAK HEATER-CATHODE VOLTAGE:

Heater negative with respect to cathode. . 200 max. volts
Heater positive with respect to cathode. . 200^b max. volts

Typical Operation as Resistance-Coupled Amplifier:

See *RESISTANCE-COUPLED-AMPLIFIER CHART No. 25*
at front of this Section


^a Without external shield.

^b The dc component must not exceed 100 volts.



20EZ7

AVERAGE PLATE CHARACTERISTICS Each Unit



92CM-10804




RADIO CORPORATION OF AMERICA
Electron Tube Division
Harrison, N. J.

DATA 2
10-60

20EZ7

AVERAGE CHARACTERISTICS Each Unit



92CM-10805

RADIO CORPORATION OF AMERICA
Electron Tube Division

Harrison, N. J.

